


AVIATION & INDUSTRIAL N.D.T. SUPPLIES

Division of Ezy Spray Manufacturers Pty. Ltd. (Inc. in Victoria)

A.B.N. 75 004 816 399

A.C.N. 004 816 399



13 Island View Drive, (P.O. Box 33)
Tyabb, Victoria, 3913, Australia.

Telephone: 61 (0) 3 5977 4088

Fax: 61 (0) 3 5977 4093

Email: ezyspray@bigpond.com

Material Safety Data Sheet

DR60 SOLVENT CLEANER/REMOVER (aerosol)

STATEMENT OF HAZARDOUS NATURE

Classified as hazardous according to the criteria of Worksafe Australia

Page 1 of 2

Date issued: June 2006

Version No: 2

EMERGENCY CONTACTS

Normal Office Hours-Mon-Fri 8.30am-5.00pm (03) 5977 4088 Poisons Information Centre (24 hours) 13 11 26

PRODUCT IDENTIFICATION

PRODUCT NAME: DR60 Solvent Cleaner/Remover

UN No: 1950

Subsidiary Risk: N/A

EPG No: 2A2

HAZCHEM: 2WE

DG.Class: 2

Packing Group: N/A

Poisons Sch: S5

USE/APPLICATION: Solvent based dye remover/cleaner

INGREDIENTS

Hydrocarbon propellant (butane)

CAS No.

% IN PRODUCT

Acetone

106-97-8

20-40

Isopropanol

67-64-1

20-40

67-63-0

20-40

PHYSICAL DESCRIPTION/PROPERTIES

APPEARANCE AND ODOUR: Clear liquid with slightly sweet odour

BOILING POINT:(°C): N/A

pH: N/A

VAPOUR PRESSURE (Kpa @ 20°C): approx 350

SOLUBILITY IN WATER: miscible

SPECIFIC GRAVITY (g/cm³): 0.8 approx

AUTOIGNITION TEMP (°C): N/D

FLAMMABILITY LIMITS%: LEL 1.8 UEL 9.5

FLASH POINT (°C): -60 approx

HEALTH HAZARD INFORMATION

ACUTE AND CHRONIC EFFECTS OF OVEREXPOSURE

EYES: Contact may result in irritation, pain and redness.

SKIN: Contact may result in defatting of the skin and moderate irritation.

INHALED: Moderate toxicity-narcotic. Over exposure may result in upper respiratory irritation, nausea, dizziness and vomiting.

SWALLOWED: Harmful. Ingestion may result in nausea, vomiting, and possible lung damage.

FIRST AID PROCEDURES

EYES: Flush with water for 15 minutes. Seek medical attention if symptoms persist.

SKIN: Remove contaminated clothing. Flush affected area with soap and water. Seek medical attention if irritation develops.

INHALED: Leave area of exposure immediately. If victim is not breathing apply artificial respiration and seek medical assistance.

SWALLOWED: Do not induce vomiting. If poisoning occurs seek immediate medical attention.

FIRST AID FACILITIES: A source of water or eyewash bottle should be nearby.

DR60 SOLVENT CLEANER/REMOVER (aerosol)

Page 2 of 2.

Date issued: June 2006

Version No: 2

ADVICE TO DOCTOR

Treat symptomatically

PRECAUTIONS FOR USE

EXPOSURE LIMITS: It is advisable to control exposure levels to below 10mg/m³

ENGINEERING CONTROLS: Adequate ventilation is required to keep below exposure limits.

PERSONAL PROTECTION:

GLOVES: Wear impervious gloves if a risk of contact exists.

PROTECTIVE CLOTHING: Wear coveralls when using regularly.

EYE PROTECTION: Wear splash proof goggles if a risk of contact exists.

RESPIRATORY PROTECTION: Not normally required in well-ventilated areas

FLAMMABILITY: Product is flammable.

SAFE HANDLING INFORMATION

STORAGE: Avoid ignition sources. Store in a well-ventilated area in accordance with the statutory requirements for the storage of aerosols using liquefied flammable gas as a propellant

TRANSPORT: Transport in accordance with the ADG Code requirements for aerosols, Class 2.1 dangerous goods.

SPILLS: Absorb spill with sand or other inert absorbent and place in sealed containers for disposal.

DISPOSAL: Do not incinerate. Dispose of unwanted product in accordance with State statutory regulations.

FIRE AND EXPLOSION HAZARD: Product has a flammable vapour and has hazards typical of aerosols using liquefied petroleum gas as a propellant. Containers can be over-pressurised if subjected to high temperatures.

EXTINGUISHING MEDIA: Use a dry agent, carbon dioxide or foam.

FIRE FIGHTING PROCEDURES: For fires involving large amounts wear full protective equipment and fight from upwind.

UNUSUAL FIRE/EXPLOSION HAZARDS AND DECOMPOSITION PRODUCTS: Product is readily ignited.

INCOMPATIBILITY: Avoid contact with oxidising agents and spontaneously combustible substances.

OTHER INFORMATION

Abbreviations: N/D-Not determined.

N/A-Not applicable.

This MSDS is valid for 5 years from the date of issue. However, this version may be revoked and revised at any time and users should contact Aviation and Industrial NDT Supplies to ensure they are in possession of the latest version.

Contact Point: (03) 5977 4088 Business Hours.

All statements, technical information and recommendations contained herein are based on available scientific tests or data, that we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our product, or the products of other manufactures in combination with our products, may be used. Aviation and Industrial NDT Supplies assume no liability or responsibility for loss or damage resulting from the improper use or handling of its products, from incompatible product combinations, or from the failure to follow instructions, warnings and advisories in the product's label and Material Safety Data Sheet.