

SPECTROLINE®

AccuMAX™ XS-555/L Luminance Sensor Detector

The perfect accessory for the AccuMAX XRP-3000 Digital Radiometer/Photometer Kit. Ideal for technicians performing radiographic examinations.

Luminance is typically used to measure uniformly radiating surfaces, such as backlit panels, film viewers and monitors. The AccuMAX XS-555/L luminance sensor detector measures the brightness of a visible light source and, unlike many competitive units, allows the user the choice of displaying the results in three distinct units of measure: candelas per square meter (cd/m^2), candelas per square foot (cd/ft^2) and footlamberts (fL).

Features

- Meets ASTM and MIL standards.
- Extremely versatile. Provides luminance measurements in cd/m^2 , cd/ft^2 and fL.
- Ideal for radiographic examinations requiring film viewer output measurements.
- Connects easily to the digital readout unit via a USB cable.



Specifications

Dimensions

Height	3.2 in (8.1 cm)
Length	3.0 in (7.6 cm)
Width	2.1 in (5.3 cm)
Weight	6.4 oz (181g)

Luminance Range

0-1,000,000 cd/m^2
0-90,000 cd/ft^2
0-285,000 fL

Sensor detector connects easily to readout unit using any standard USB cable (left) or the Spectroline XCB-100 water-resistant sensor adapter cable (right).

SPECTRONICS CORPORATION
956 Brush Hollow Road, P.O. Box 483
Westbury, New York 11590
800-274-8888 • 516-333-4840
Fax: 800-491-6868 • 516-333-4859
www.spectroline.com

RFS

Russell Fraser Sales Pty Ltd

Unit 8/29 Waratah St
Kirrawee NSW 2232

Ph: (02) 9545 4433
Fax: (02) 9545 4218

e-mail rfs@rfsales.com.au
web: www.rfsales.com.au

ABN: 79 071 258 549